



MULTAGRI MS 15W-40



Multipurpose oil adapted to the lubrication of different systems of agricultural machineries.

SPECIFICATIONS AND APPROVALS

International specifications	ACEA E2	API CF-4/CE/SF	API GL-4
Manufacturers' approvals	Meets the requirements of		
✓ Massey-Ferguson CMS M 1145/ M 1144	✓ Engines : Ford M2C 159B3, Massey Ferguson CMS M1139, John Deere JDM J27		
✓ ZF TE-ML 06B/07B	✓ Transmissions : John Deere JDM J20A/C, Ford M2C86A, M2C134D, FNHA 2C 201.00, Massey Ferguson CMS M1127A, M1135		
	✓ Automatic transmissions : GM Allison C4		

APPLICATIONS

TOTAL MULTAGRI MS 15W-40 is designed for turbocharged or naturally-aspirated Diesel engines. This lubricant is also adapted to mechanical transmissions, gearboxes, reduction drives, bevel gears requiring API GL-4 / MIL.L.2105 SAE 80W-90 performance.

TOTAL MULTAGRI MS 15W-40 is recommended for:

- ✓ Mechanical transmissions fitted with oil bath brakes
- ✓ Hydraulic lift and assistance circuits
- ✓ Power take-offs and multidisc clutches operating in oil
- ✓ Hydrostatic steering systems

PERFORMANCES AND CUSTOMER BENEFITS

TOTAL MULTAGRI MS 15W-40 exhibits lots of advantages and properties:

- ✓ High viscosity when hot, guaranteeing continuous lubrication in the engine and on gears and hydraulic components
- ✓ Outstanding anti-wear properties ensuring longer mechanical components durability
- ✓ Extreme-pressure properties allow lubrication of transmissions requiring oil type API GL4 or MIL.L.2105 SAE 80W-90
- ✓ Anti-corrosion additives protect the non-ferrous metals in the engine and other systems.
- ✓ Excellent anti-foaming properties, to prevent any sump overflow or cavitation
- ✓ Completely inert to seals
- ✓ Special frictional characteristics ensuring progressive, efficient and silent operation of brake and clutch systems
- ✓ Reduction of the number of lubricants needed on a farm

PHYSICAL AND CHEMICAL CHARACTERISTICS*

TOTAL MULTAGRI MS 15W-40		Method	Value
Density at 15°C	kg/m ³	ASTM D1298	888
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	99.4
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	13.5
Viscosity Index	-	ASTM D2270	135
Pour Point	°C	ASTM D97	-39

* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.

TOTAL LUBRIFIANTS

562, avenue du Parc de l'Île
92029 Nanterre cedex
FRANCE

TOTAL MULTAGRI MS 15W-40

Update 10/2014

www.lubricants.total.com



This lubricant does not cause adverse health effects when used in the intended application.

A safety datasheet is accessible on request from your local dealer or on the website www.quickfds.com